

EVERGREEN

drive to the future



**DYNACOMFORT
EH226**

PASSENGER CAR | HIGH PERFORMANCE

HIGH PERFORMANCE

HP tires from EVERGREEN are engineered to accommodate the increased power, reinforced brakes, and sport-tuned suspension systems found in modern vehicles. With a lower aspect ratio for increased tread width and a speed rating of H or higher for added stability, these tires offer optimal performance and safety.

DYNAComfort EH226



DynaComfort EH226 is a high-performance tire that delivers exceptional traction and handling on both wet and dry surfaces. With lower rolling resistance and improved fuel efficiency, this tire is both cost-effective and environmentally friendly.

T/H/V/W Rated
U.T.Q.G 400/A/A
45/50/55/60/65/70 Series



ECONOMY AND COMFORT

DynaComfort EH226 is a tire that provides a comfortable driving experience without sacrificing fuel efficiency. Featuring exceptional cornering stability and longer tread life, this tire delivers outstanding value for drivers seeking a balance of comfort and economy.



Longer Tire Life

EH226 is formulated with a special blend that improves its resistance to wear and tear. It is designed to increase the lifespan of the product and enhance its performance over time.

Comfort

The streamlined pattern design is engineered for a smooth and comfortable ride, minimizing road noise, and remarkable high-speed stability.



Fuel Efficient

The utilization of a sidewall compound with high hardness helps to prevent deformation of the tire, reduces the contact area with the ground, lowers rolling resistance, and results in improved fuel efficiency.






HANDLING

DynaComfort EH226 is a reliable and versatile tire that offers exceptional handling on both wet and dry surfaces. Designed for high performance, this tire delivers superior grip and control, providing drivers with a comfortable and safe ride.

Optimized Structure

Reinforced shoulder blocks and central grooves enhance grip on the road and improve control during cornering and swerving



Asymmetric Pattern Design

The unique asymmetric pattern design increases tire rigidity and creates improved stability for steering and handling.



Traction

The high-density groove design efficiently cuts through the water film, combined with the contour design of CATR technology, effectively drains water.



**DynaComfort
EH226**



Inch	Size	LI / SI	Overall Diameter		Section Width		Standard Rim	Max. Load	Max. Pressure
			mm	inch	mm	inch		kg	kpa
13"	155/70R13	75T	548	21.6	157	6.2	4.50B	387	300
	165/65R13	77T	544	21.4	170	6.7	5.00B	412	300
	175/60R13	77H	540	21.3	177	7.0	5.00B	412	300
	175/70R13	82T	576	22.7	177	7.0	5.00B	475	300
14"	155/65R14 XL	79T	558	22.0	157	6.2	4½J	437	340
	165/60R14	75H	554	21.8	170	6.7	5J	387	300
	165/70R14	81T	588	23.1	170	6.7	5J	462	300
	165/70R14 XL	85T	588	23.1	170	6.7	5J	515	340
	175/65R14	82T	584	23.0	177	7.0	5J	475	300
	175/65R14 XL	86T	584	23.0	177	7.0	5J	530	340
	175/70R14 XL	88T	602	23.7	177	7.0	5J	560	340
	185/60R14	82H	578	22.8	189	7.4	5½J	475	300
	185/65R14	86H	596	23.5	189	7.4	5½J	530	300
	185/70R14	88H	616	24.3	189	7.4	5½J	560	300
	205/60R14	88H	602	23.7	209	8.2	6J	560	300
15"	155/60R15	74H	567	22.3	157	6.2	4½J	375	300
	165/65R15	81T	595	23.4	170	6.7	5J	462	300
	175/60R15	81V	591	23.3	177	7.0	5J	462	300

Inch	Size	LI / SI	Overall Diameter		Section Width		Standard Rim	Max. Load	Max. Pressure
			mm	inch	mm	inch		kg	kpa
15"	175/65R15	84H	609	24.0	177	7.0	5J	500	300
	185/55R15	82V	585	23.0	194	7.6	6J	475	300
	185/60R15	84H	603	23.7	189	7.4	5½J	500	300
	185/60R15 XL	88H	603	23.7	189	7.4	5½J	560	340
	185/65R15	88H	621	24.4	189	7.4	5½J	560	300
	195/50R15	82V	577	22.7	201	7.9	6J	475	300
	195/55R15	85V	595	23.4	201	7.9	6J	515	300
	195/60R15	88V	615	24.2	201	7.9	6J	560	300
	195/65R15	91H/V	635	25.0	201	7.9	6J	615	300
	205/55ZR15	88W	607	23.9	214	8.4	6½J	560	300
	205/65R15	94V	647	25.5	209	8.2	6J	670	300
16"	185/50R16	81V	592	23.3	194	7.6	6J	462	300
	185/55R16 XL	87V	610	24	194	7.6	6J	545	340
	195/45ZR16 XL	84W	582	22.9	195	7.7	6½J	500	340
	195/50R16 XL	88V	602	23.7	201	7.9	6J	560	340
	195/55R16	87V	620	24.4	201	7.9	6J	545	300
	195/55R16 XL	91V	620	24.4	201	7.9	6J	615	340
	205/55R16 XL	94V	632	24.9	214	8.4	6½J	670	340
	205/60R16	92V	652	25.7	209	8.2	6J	630	300
	205/65R16	95H	672	26.5	209	8.2	6J	690	300
	225/60R16 XL	102V	676	26.6	228	9	6½J	850	340
	235/60R16	100V	688	27.1	240	9.4	7J	800	300

EVERGREEN TIRE

Add: Building No. 5, Lane 388 Daduhe Road,
Shanghai 200062, China

Tel: (+86) (21) 6295 5670

E-mail: evergreentyre@evergreentyre.com

www.evergreentyre.com