

# ***LineRoute*** ***ESL01***

ESL01 is the latest generation of high-performance steering tire for national and regional operations.



LONGEVITY



SAFETY



GREEN

**EVERGREEN**

*drive to the future*



# LineRoute ESL01



## Features

- Advanced silica-rich cap and base compounds
- Optimized 5-rib cap design with optimal pressure distribution
- Enhanced 4-belt construction design
- Increased tread width and contact surface area
- Stone ejection system with waved grooves

## Benefits

- Provides longer tire life with excellent fuel efficiency and wet grip
- Provides good steering stability, high mileage and even wear.
- Maximum safety and retreadability
- Extended wear life and mileage potential
- Eliminates stone retention for extended tire life

## Size

| Size        | PR | LI/SS    | Type | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Tread Depth (mm) | Load  |       | Pressure |        |
|-------------|----|----------|------|--------------|-----------------------|--------------------|------------------|-------|-------|----------|--------|
|             |    |          |      |              |                       |                    |                  | S(kg) | D(kg) | S(kPa)   | D(kPa) |
| 11R24.5     | 16 | 149/146L | T/L  | 8.25         | 1104                  | 279                | 16.5             | 3250  | 3000  | 830      | 830    |
| 12R22.5     | 18 | 152/149L | T/L  | 9.00         | 1085                  | 300                | 17.5             | 3550  | 3250  | 930      | 930    |
| 275/70R22.5 | 16 | 148/145M | T/L  | 8.25         | 958                   | 275                | 15               | 3150  | 2900  | 900      | 900    |
| 295/60R22.5 | 18 | 150/147L | T/L  | 9.00         | 926                   | 295                | 16               | 3350  | 3075  | 900      | 900    |
| 295/75R22.5 | 14 | 144/141L | T/L  | 9.00         | 1014                  | 298                | 16.5             | 2800  | 2575  | 760      | 760    |
| 295/75R22.5 | 16 | 146/143L | T/L  | 9.00         | 1014                  | 298                | 16.5             | 3000  | 2725  | 830      | 830    |
| 315/80R22.5 | 20 | 156/153L | T/L  | 9.00         | 1076                  | 312                | 16.5             | 4000  | 3650  | 850      | 850    |