

**EVERGREEN**

*drive to the future*

# ***LineRoute*** ***EDL16***

EDL16 is the drive tire for long haul operations with excellent anti-wear, grip, and durability performance.



CONTROL



LONGEVITY



GREEN



# LineRoute **EDL16**

▲ Recommend



## Features

Advanced tread compound

Robust tread design

Stone ejection system

Optimal heat dissipation structure

## Benefits

- ▶ Enhances wear resistance, ensuring superior performance over long distances and maximizing tire lifespan.
- ▶ Ensures strong traction and reliable performance.
- ▶ Effectively expels stones and debris, minimizing the risk of damage and extending tire life.
- ▶ Minimizes heat buildup, promoting longer tire life and consistent performance over extended distances.

## Size

| Size        | PR | LI/SS    | Type | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Tread Depth (mm) | Load  |       | Pressure |        | Plant |
|-------------|----|----------|------|--------------|-----------------------|--------------------|------------------|-------|-------|----------|--------|-------|
|             |    |          |      |              |                       |                    |                  | S(kg) | D(kg) | S(kPa)   | D(kPa) |       |
| 11R22.5     | 16 | 146/143L | T/L  | 8.25         | 1050                  | 279                | 23.0             | 3000  | 2725  | 830      | 830    | VN    |
| 11R22.5     | 18 | 148/145L | T/L  | 8.25         | 1050                  | 279                | 23.0             | 3000  | 2725  | 830      | 830    | CN    |
| 295/75R22.5 | 16 | 146/143L | T/L  | 9.00         | 1020                  | 298                | 23.0             | 3000  | 2725  | 830      | 830    | CN VN |
| 11R24.5     | 16 | 149/146L | T/L  | 8.25         | 1116                  | 279                | 23.0             | 3250  | 3000  | 830      | 830    | CN VN |
| 285/75R24.5 | 16 | 147/144L | T/L  | 8.25         | 1056                  | 283                | 24.0             | 3075  | 2800  | 830      | 830    | VN    |

**EVERGREEN**

*drive to the future*

# **MultiRoute** **EDR53**

Built for demanding regional drive applications, the EDR53 delivers long-lasting performance, dependable traction, and retreadable value mile after mile.



LONGEVITY



SAFETY



CONTROL



# MultiRoute EDR53

▲ Recommend



## Features

Directional Tread Design

Wide Contact Patch with Deep Tread

Reinforced Shoulder Tie Bars

Improved Handling and Grip

Extended Tire Life

Smoother, More Stable Ride

## Benefits

- Unidirectional pattern with angled blocks enhances high-speed stability and promotes efficient stone ejection.
- Broad tread footprint increases traction and lateral stability, while deeper grooves extend tread life.
- Shoulder blocks are connected by tie bars to reduce tread deformation and resist irregular wear.
- Enhanced road contact ensures reliable traction on both dry and slippery regional roads.
- Deep tread and optimized wear resistance contribute to longer original mileage and better value.
- Staggered tread blocks and structural rigidity reduce vibration for improved ride comfort.

## Size

| Size        | PR | LI/SS    | Type | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Tread Depth (mm) | Load  |       | Pressure |        | Plant |
|-------------|----|----------|------|--------------|-----------------------|--------------------|------------------|-------|-------|----------|--------|-------|
|             |    |          |      |              |                       |                    |                  | S(kg) | D(kg) | S(kPa)   | D(kPa) |       |
| 295/80R22.5 | 18 | 152/149L | T/L  | 9.00         | 1044                  | 298                | 21.5             | 3550  | 3250  | 900      | 900    | VN    |
| 315/70R22.5 | 18 | 156/150L | T/L  | 9.00         | 1014                  | 312                | 19.5             | 4000  | 3350  | 900      | 900    | VN    |
| 315/80R22.5 | 20 | 156/153K | T/L  | 9.00         | 1076                  | 312                | 22.0             | 4000  | 3650  | 850      | 850    | CN VN |